

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 1 143 645 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
10.10.2001 Bulletin 2001/41

(51) Int Cl. 7: H04B 10/17

(21) Application number: 01301940.1

(22) Date of filing: 02.03.2001

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Yokoyama, Ryu, Nec Corporation  
Tokyo (JP)

(74) Representative: Moir, Michael Christopher et al  
Mathys & Squire  
100 Gray's Inn Road  
London WC1X 8AL (GB)

(30) Priority: 02.03.2000 JP 2000057290


(71) Applicant: NEC CORPORATION  
Tokyo (JP)

(54) Optical amplifier, optical amplifying repeater and transmission apparatus for wavelength-division-multiplexed signal light

(57) Flatness of a gain (optical output level) is maintained even when wavelength-division-multiplexed signal light (WDM signal light) is optically amplified utilizing a Raman amplification function. The optical amplifier comprises: two (first and second) pumping light sources for Raman amplification for outputting first and second pumping lights; wavelength multiplexers for Raman amplification for allowing the first and second pumping lights to be incident on optical fiber transmission paths, where the WDM signal light propagates, in the direction opposite to the propagation direction of the signal light. The signal lights are Raman-amplified by the pumping

lights. A wavelength of the first pumping light is set such that the gain of the Raman-amplified signal light declines in one direction, and, on the other side, the wavelength of the second pumping light is set such that the gain declines in the other direction. Gradients for showing a relation between the wavelength and the gain in Raman amplification by the first and second pumping lights are made to be in opposite directions from each other. Optical output levels and the wavelengths of the first and second pumping lights are set such that the gains for the signal lights included in the Raman-amplified WDM signal light become substantially equal to one another.

Fig. 1



## Description

### BACKGROUND OF THE INVENTION

#### Field of the Invention

**[0001]** The present invention relates to an optical amplifier that amplifies a signal light based on a Raman amplification function, and to an optical amplifying repeater and an optical transmission apparatus that are constituted by using the optical amplifier. More particularly, the present invention relates to an optical amplifier that amplifies collective signal light, which signal light has a plurality of different wavelengths which are wavelength-division-multiplexed (hereinafter referred to as WDM signal light), and to an optical amplifier that includes a flattening gain function for each signal light.

#### Description of the Related Art

**[0002]** It is known that a Raman amplification function is generated by allowing a pumping light having a specified wavelength to be incident on a signal light that propagates in an optical fiber transmission path, and that thereby an optical amplification of the signal light can be performed (for example, refer to Japanese Patent Laid-Open No. 10/022931 (1998 Gazette)). The optical amplification by Raman amplification is performed by allowing the pumping light having the specified wavelength to be incident on the optical fiber transmission path in an opposite direction to a progress direction of the signal light that propagates in the optical fiber transmission path.

**[0003]** The optical amplification utilizing a Raman amplification function could be utilized independently. However, in most cases, it is normally used in combination with optical amplification which has a rare-earth-element-doped optical fiber as an amplification medium (hereinafter referred to as normal optical amplification). In an optical amplifying repeater arranged midway or at an output end of an optical fiber transmission path, and in a front optical amplifier arranged within an optical reception terminal station, pumping light for performing Raman amplification is used with the normal optical amplification to improve the gain.

**[0004]** However, when the optical amplification is performed on the WDM signal light by a Raman amplification function, a difference (deviation) occurs in optical output levels of each signal light included in the WDM signal light after the optical amplification, since the gain of Raman amplification has a wavelength dependency. With regard to the difference of the optical output level, the differences are added in the multi-step optical amplification and repeating transmission system, resulting in large influences to a transmission characteristic.

**[0005]** Generally, an output-wavelength characteristic of the optical amplifier as described above is designed in a state such that the WDM signal light to be

input does not have the wavelength deviation in the optical output level. However, the WDM signal light, on which the optical amplification was performed by a Raman amplification function generated in the optical fiber transmission path connected to an input portion of the optical amplifier, further undergoes the normal optical amplification. Therefore, at the time when the WDM signal light is input to the optical amplifier, when the deviation exists in optical input levels among the signal lights included in the WDM signal light, the deviation is further increased by the normal optical amplification. As a result, a desired output wavelength characteristic cannot be obtained.

**[0006]** The gain by Raman amplification varies depending on the wavelength of signal light having wavelength dependency, and the wavelength dependency itself is dependent on the wavelength of a pumping light source. Accordingly, there is a problem of difficulties in controlling the wavelength characteristic of the signal light uniformly, due to scattering of the wavelength at the time of manufacturing the pumping light source, wavelength fluctuation according to difference in pumping light intensity, the temperature at which the pumping light source is used, and other factors.

### SUMMARY OF THE INVENTION

**[0007]** The object of the preferred embodiments of the present invention is to maintain uniformity in the gain even when the optical amplification is performed on WDM signal light by optical amplification utilizing a Raman amplification function. Moreover, another object is to make the optical output level of each signal included in the WDM signal light uniform.

**[0008]** The object of the preferred embodiments of the optical transmission apparatus of the present invention is to perform a stable optical transmission such that a large deviation does not occur in the optical output level of each signal light, even in the case when signal light is transmitted.

**[0009]** The optical amplifier of the present invention comprises: a first pumping light source for Raman amplification, which outputs a first pumping light having a first wavelength; a second pumping light source for Raman amplification, which outputs a second pumping light having a second wavelength; and a wavelength multiplexer for Raman amplification, which allows the first and second pumping lights to be incident on the optical fiber transmission path where the signal light propagates. The signal light is Raman-amplified in the optical fiber transmission path by the first and second pumping lights. A propagation direction of the first and second pumping lights may be backward or may be forward (the same direction) to that of the signal lights.

**[0010]** Although the signal light may be applied to a single signal light, it is, specifically, the WDM signal light, in which the signal lights having a plurality of wavelengths different from each other are wavelength-divi-

sion-multiplexed. In other words, the optical amplifier of the present invention, with regard to the pumping light for performing Raman amplification, allows two pumping lights having the wavelengths different from each other to be incident on the optical transmission path.

**[0011]** In the above-described constitution, to reduce the influence on the WDM signal light from the wavelength dependency of the gain, which occurs when optical amplification by Raman amplification is performed, the first wavelength is the wavelength to allow the signal light to be Raman-amplified such that the wavelength having the peak gain by Raman amplification becomes shorter than the wavelength of the signal light included in the WDM signal light. On the other hand, the second wavelength is the wavelength to allow the signal light to be Raman amplified such that the wavelength having the peak gain by Raman amplification becomes longer than the wavelength of the signal light included in the WDM signal light.

**[0012]** Herein, a gradient showing the relation between the wavelength and the gain in Raman amplification by the first pumping light and a gradient showing the relation between the wavelength and the gain in Raman amplification by the second pumping light are in opposite directions from each other. The optical output level and the wavelength of the first and second pumping lights are respectively set such that the gains for signal lights included in the WDM signal light, on which Raman amplification was performed by the first and second pumping lights, become substantially equal to each other.

**[0013]** In the above-described constitution, the first and second pumping light sources for Raman amplification can be constituted of: first and second laser diodes that oscillate first and second lights respectively; and first and second fiber gratings, which are arranged in a previous step of the first and second laser diodes, that selectively transmit the lights having the first and second wavelengths in a specified ratio and reflect residual light. Alternatively, the first and second pumping light sources for Raman amplification can be also constituted of: the first and second laser diodes that oscillate the first and second lights respectively; and first and second optical filters, which are arranged in a previous step of the first and second laser diodes, that selectively transmit the lights having the first and second wavelengths.

**[0014]** The wavelength multiplexer in the optical amplifier for Raman amplification of the present invention, more particularly, can be constituted of: first and second pumping light multiplexers for Raman amplification, which are arranged by connecting to an optical fiber connected to the optical fiber transmission path, that transmit the signal light and allow the first and second pumping lights to be incident on the optical fiber. Alternatively, the wavelength multiplexer can be constituted of: a pumping light multiplexer for Raman amplification, which multiplexes the first and second pumping lights and outputs a multiplexed pumping light; and a pumping

light multiplexer for Raman amplification, which is arranged by connecting to the optical fiber connected to the optical fiber transmission path, that transmits the signal light and allows the multiplexed pumping light to be incident on the optical fiber. Moreover, the wavelength multiplexer can be also constituted of: a polarization combiner for Raman amplification; and a pumping light multiplexer for Raman amplification. The former performs the polarization combination of the first and second pumping lights and outputs the multiplexed pumping light, where the first and second pumping lights, which are respectively output from the first and second pumping light sources for Raman amplification, are perpendicular to each other, that is, in a polarization state. The latter, which is arranged by connecting to the optical fiber connected to the optical fiber transmission path, transmits the signal light and allows the multiplexed pumping light to be incident on the optical fiber.

**[0015]** For the purpose of improving uniformity of the gain of the signal light included in the WDM signal light or the optical output level itself, a constitution can be adopted where a feedback control is performed to the optical amplification by Raman amplification function, which is obtained by the above-described constitution.

Specifically, in addition to the above-described constitution, the wavelength multiplexer is further allowed to comprise: an optical splitter for splitting a part of the WDM signal light and outputs the split WDM signal light; signal light extractor to extract two signal lights, which have the wavelengths different from each other, from each signal light included in the split WDM signal light; an optical receiver to detect the optical output level of each of the two signal lights extracted by the signal light extractor; and a pumping light output control circuit for controlling the optical output levels or the wavelengths of the first and second pumping lights for Raman amplification according to the amount of difference between the two optical output levels.

**[0016]** Although the above-described optical amplifier of the present invention has an independent optical amplification function only by Raman amplification function, it can be also used in combination with the normal optical amplification function, in which the optical amplification is performed by using the rare-earth element doped optical fiber (for example, an erbium doped fiber) as the amplification medium. Specifically, in the above-described optical amplifier, the optical amplification by Raman amplification and the normal optical amplification are used in combination by further comprising: an amplification medium for amplifying the signal light; a third pumping light source for outputting a third pumping light to allow the amplification medium to be in an excited state; and a wavelength multiplexer for allowing the third pumping light to be incident on the amplification medium.

**[0017]** The wavelength multiplexer in such a constitution may be arranged at a position from which the signal light is input to the amplification medium, and the third

pumping light may be allowed to be incident on the amplification medium in the same direction as the propagation direction of the signal light. Alternatively, the wavelength multiplexer may be arranged at an output side of the amplification medium from which the signal light is output, and the third pumping light is allowed to be incident on the amplification medium in the opposite direction to the propagation direction of the signal light. On the side to which the signal light of the wavelength multiplexer for Raman amplification is output, an optical isolator may be arranged, which selectively transmits only the light propagating to the same direction as that of the signal light and obstructs the light propagating in the opposite direction. According to such constitution, a reflected returning light or the influence by the pumping light for Raman amplification, which comes from the optical amplifier arranged in a subsequent step, is reduced, thus more stable optical amplification can be performed.

**[0018]** The constitution of the feedback control for the purpose of obtaining uniformity of the gain of the signal light included in the WDM signal light or of the optical output level itself can be also applied to the constitution where the normal optical amplification is used in combination. Specifically, in addition to the above-described constitution, the optical amplifier is further allowed to comprise: the optical splitter for splitting a part of the WDM signal light and outputs the split WDM signal light; the signal light extractor to extract two signal lights, which have the wavelengths different from each other, from each signal light included in the split WDM signal light; the optical receiver for detecting the optical output level of each of the two signal lights extracted by the signal light extractor; and the pumping light output control circuit for controlling the optical output levels or the wavelengths of the first and second pumping lights for Raman amplification according to the amount of difference between the two optical output levels.

**[0019]** The optical splitter may be arranged at a position from which the WDM signal light is input to the wavelength multiplexer for Raman amplification. Alternatively, the optical splitter may be arranged at a position to which the WDM signal light is output from the wavelength multiplexer for Raman amplification. In the case of the former constitution, the feedback control is performed intended for the flatness of the WDM signal light immediate before it is input to the optical amplifier. On the other hand, in the case of the latter constitution, the feedback control is performed intended for the uniformity of the WDM signal light after the optical amplification.

**[0020]** The optical amplifying repeaters of the present invention are arranged midway of upper and lower lines, and perform optical repeating and amplification for the signal lights propagating in each direction. As a basic constitution, the above-described optical amplifying repeaters are constituted to be arranged in each of the upper and lower lines. Specifically, the optical amplifying repeater is the one that comprises: the optical amplifier

for a down signal, which is arranged in the optical transmission path for the down signal; and the optical amplifier for an up signal, which is arranged in the optical transmission path for the up signal. The optical amplifiers for down and up signals comprise the optical amplifiers of the present invention as described above.

**[0021]** In the above-described constitution, two of the pumping light sources for Raman amplification may be provided for each of the upper and lower lines. For more efficient constitution, the first pumping light source for Raman amplification, which is provided in the optical amplifier for the down signal and the first pumping light source for Raman amplification, which is provided in the optical amplifier for the up signal use a common first pumping light source for Raman amplification. And, the second pumping light source for Raman amplification, which is provided in the optical amplifier for the down signal and the second pumping light source for Raman amplification, which is provided in the optical amplifier for the up signal use a common second pumping light source for Raman amplification. The first and second pumping lights for Raman amplification output from the common first and second pumping light sources for Raman amplification may be coupled and split by an optical coupler, and then the split lights may be respectively output to the wavelength multiplexer for Raman amplification, which is provided in the optical amplifier for the down signal and to the wavelength multiplexer for Raman amplification, which is provided in the optical amplifier for the up signal. Such a constitution can be adopted in the case of the optical amplification performed independently by Raman amplification as well as in the case where the normal optical amplification is used in combination.

**[0022]** In the constitution where the normal optical amplification is used in combination, the optical amplifiers for the down and up signals further respectively comprise fourth pumping light sources for outputting a fourth pumping light to allow the amplification medium to be in the excited state. The third pumping light source provided in the optical amplifier for the down signal and the third pumping light source provided in the optical amplifier for the up signal are made to be a common third pumping light source. The fourth pumping light source provided in the optical amplifier for the down signal and the fourth pumping light source provided in the optical amplifier for the up signal are made to be a common fourth pumping light source. The third pumping light output from the common third pumping light source and the fourth pumping light output from the common fourth pumping light source are coupled and split by an optical splitting coupler, and the split lights may be respectively output to the wavelength multiplexers provided in the optical amplifiers for the down and up signals.

**[0023]** The WDM signal light transmission apparatus of the present invention comprises: an optical transmission terminal station for wavelength division multiplexing a plurality of signal lights having the wavelengths

different from each other and for sending out the WDM signal light; the optical fiber transmission path for propagating the WDM signal light; an optical receiving terminal station for receiving the WDM signal light; and the optical amplifier of the present invention, which is arranged midway of the optical transmission path to repeat and amplify the WDM signal light.

[0024] Similarly, the WDM signal light transmission apparatus, which has the upper and lower lines, for transmitting the WDM signal light in both directions comprises: the optical transmission terminal station for wavelength division multiplexing a plurality of down signal lights having the wavelengths different from each other and for sending out a down WDM signal light; the optical fiber transmission path for the down signal light for propagating the down WDM signal light; the optical receiving terminal station for the down signal light for receiving the down WDM signal light; the optical transmission terminal station for wavelength division multiplexing a plurality of up signal lights having the wavelengths different from each other and for sending out an up WDM signal light; the optical fiber transmission path for the up signal light for propagating the up WDM signal light; the optical receiving terminal station for the up signal light for receiving the up WDM signal light; and the optical amplifiers of the present invention, which are arranged midway of the up and down optical transmission paths to repeat and amplify the up and down WDM signal lights.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0025] Preferred features of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:-

Fig. 1 is a view showing a constitution of a first embodiment of the optical amplifier of the present invention;

Fig. 2 is a graph for explaining a fundamental principle of the optical amplifier of the present invention, which shows a relation between wavelength and gain in Raman amplification.

Figs. 3A, 3B, 3C and 3D are graphs for explaining the fundamental principle of the optical amplifier of the present invention, and show a relationship between wavelength and an output level of WDM signal light in Raman amplification; Fig. 3A is a graph showing a relationship between the wavelength and output level of the WDM signal light before Raman amplification, Figs. 3B and 3C shown relationships between the wavelength and output level of the WDM signal light when an independent Raman amplification is performed, and Fig. 3D shows a final relationship between the wavelength and output level of the WDM signal light;

Fig. 4 is a view showing the first embodiment of the present invention, which shows a variation example

of the optical amplifier shown in Fig. 1;

Fig. 5 is a view exemplifying a constitution of the pumping light for Raman amplification that is performed in the optical amplifier of the present invention;

Fig. 6 is a view exemplifying another constitution of the pumping light for Raman amplification that is performed in the optical amplifier of the present invention;

Fig. 7 is a view showing the constitution of a second embodiment of the optical amplifier of the present invention;

Fig. 8 is a view showing the constitution of a third embodiment of the optical amplifier of the present invention;

Fig. 9 is a view showing the constitution of a fourth embodiment of the optical amplifier of the present invention;

Fig. 10 is a view showing the constitution of a fifth embodiment of the optical amplifier of the present invention;

Fig. 11 is a view showing the constitution of a first embodiment of the optical amplification repeater of the present invention;

Fig. 12 is a view showing the constitution of a second embodiment of the optical amplification repeater of the present invention;

Fig. 13 is a view showing the constitution of a third embodiment of the optical amplification repeater of the present invention;

Fig. 14 is a view showing the constitution of a first embodiment of the WDM light signal transmission apparatus of the present invention; and,

Fig. 15 is a view showing the constitution of a second embodiment of the WDM light signal transmission apparatus of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0026] Next, embodiments of the optical amplifier of the present invention will be described in detail with reference to the drawings.

[0027] Fig. 1 is a view showing the constitution of the first embodiment of the optical amplifier of the present invention, which shows the fundamental principle of the optical amplifier of the present invention. The optical amplifier of the present invention comprises two pumping light sources 4 and 5 for outputting pumping lights, which have wavelengths to perform Raman amplification on the signal light propagating in an optical fiber transmission path 1.

[0028] The pumping lights output from each of the pumping light sources 4 and 5 are allowed to be incident on the optical fiber transmission path by wavelength multiplexers 2 and 3 arranged at an output end or the midway of the optical fiber transmission path 1 in the direction (the direction shown by arrows in broken lines)

opposite to a propagation direction (the direction shown by arrows in solid lines) of the signal light (the WDM signal light). In the optical amplifier of the present invention, the signal light is Raman amplified by the pumping lights respectively output from the above-described pumping light sources.

**[0029]** Herein, description will be made for reduction of influence by the wavelength dependency of the gain in Raman amplification by the optical amplifier of the present invention, that is, principle and function of flattening of the optical output level. The present invention is based on assumption of the following findings. The gain in Raman amplification has the wavelength dependency, and is characterized in that a peak gain occurs at the wavelength which is longer than that of the pumping light by a specified amount of wavelength (approximately 100 to 120nm) and gradually reducing at the wavelengths which are longer or shorter than that of the peak gain. This characteristic was confirmed in experiment or the like, and Fig. 2 schematically shows the relation between the wavelength and the gain by Raman amplification.

**[0030]** Assuming that the peak gain occurs at the wavelengths longer than that of the pumping light by approximately 80 to 110nm, when the signal light is Raman amplified by the pumping light having the wavelength  $\lambda_0$  - 90nm, the gain is characterized in that its peak occurs at the wavelength  $\lambda_0$  as indicated in Fig. 2 and gradually reduces as the wavelength goes off  $\lambda_0$ . Accordingly, the highest gain can be obtained by allowing the signal light to be Raman amplified by the pumping light having the wavelength shorter than the wavelength (hereinafter referred to as 'a center wavelength'), which is substantially the center of a wavelength range of the signal light included in the WDM signal light, by approximately 90nm.

**[0031]** However, when such Raman amplification is performed, in the case where the number of the signal lights included in the WDM signal light is large (for example, 32 waves) and the above-described wavelength region is wide, a large deviation occurs between the gains of the signal light in the vicinity of the central portion where the peak gain is obtained and the gains of the signal light in an edge portion of the wavelength range.

**[0032]** Therefore, in the optical amplifier of the present invention, Raman amplification is made to occur by two pumping lights, which are first and second pumping lights. The first pumping light has a first wavelength set such that the wavelength, at which the peak gain by Raman amplification occurs, becomes shorter than the center wavelength of the WDM signal light, and the second pumping light, on the contrary, has a second wavelength set such that the wavelength becomes longer than the center wavelength.

**[0033]** Description is now made with reference to Fig. 2. By the first pumping light, the WDM signal light is Raman amplified with the gain characteristic shown by the wavelength range A2. On the other hand, by the second

pumping light, the WDM signal light is Raman amplified with the gain characteristic shown by the wavelength range A1. In other words, the signal light is Raman amplified by each of the first and second pumping lights such that the gains have the gradients in specific directions (declining in the right and left directions). As a result of Raman amplification by the both pumping lights, the gain is made to be flat.

**[0034]** Figs. 3A, 3B, 3C and D are graphs showing relations between the wavelength and the output level of the Raman amplified WDM signal light by the optical amplifier of the present invention. Fig. 3A shows the relation between the wavelength and the output level before Raman amplification is performed, and the optical output level of each signal light included in the WDM signal light is allowed to be uniform when the optical amplifier does not have a function to perform Raman amplification. Figs. 3B and 3C show the output level of each signal light for the wavelength of the signal light when undergone the independent Raman amplification. It is understood that Fig. 3B shows the characteristic that declines in the right direction because the wavelength of the pumping light is set shorter than the center wavelength and Fig. 3C shows the opposite characteristic. Fig. 3D shows that characteristics of Figs. 3B and 3C are superposed into the final relation between the wavelength of the signal light and the optical output level, and that the deviation in the optical output level are cancelled to be uniform.

**[0035]** Next, description will be made for a variation example of the optical amplifier of the present invention.

**[0036]** Fig. 4 is a view showing the constitution of the first embodiment of the optical amplifier of the present invention, which shows the variation example of the constitution shown in Fig. 1.

**[0037]** The optical amplifier of the present invention is the one that allows the two pumping lights to be incident on the optical fiber transmission path for performing Raman amplification. The constitution for allowing the two pumping lights to be incident on the transmission path is not limited to the first embodiment shown in Fig. 1. Instead of arranging the wavelength multiplexers 2 and 3 midway of the optical fiber transmission path 1, as shown in Fig. 4, the pumping lights are previously multiplexed by the wavelength multiplexer (optical multiplexer) 2, and the multiplexed two pumping lights then may be allowed to be incident on the optical fiber transmission path 1 by the wavelength multiplexer 3 arranged midway of the optical fiber transmission path 1. This constitution is characterized in that a signal light loss is reduced owing to less number of the wavelength multiplexers arranged in the optical fiber transmission path 1.

**[0038]** Instead of the optical multiplexer 2, polarized waves output from the pumping light sources 4 and 5 are made to be in a perpendicular state with each other, and the both pumping lights may be multiplexed by a polarization multiplexer. Particularly, this constitution is suitable for the case where the wavelengths of the both

pumping lights are adjacent to each other and multiplexing by the optical multiplexer is difficult. In the above-described embodiment, the pumping lights are allowed to be incident on the optical fiber transmission path in the direction opposite to that of the signal light as shown in Fig. 1. However, the similar effect can be obtained if the pumping lights are allowed to be incident on the transmission path in the forward direction, that is, toward the subsequent step.

[0039] Next, when Raman amplification is performed by the two pumping lights as described above, the pumping lights are required to be output in a single mode at specified wavelengths. Description will be made for the constitution for realizing such pumping light.

[0040] Fig. 5 and Fig. 6 are views showing examples of the constitution of the pumping light source for Raman amplification. The constitution shown in Fig. 5 shows the one consisted of a laser diode 12 for oscillating the pumping light and a wavelength selective optical reflector (for example, a fiber grating) 13 arranged in front of the laser diode 12. Herein, the fiber grating 13 has a characteristic that it selectively reflects the pumping light of the above-described specified wavelength by a specified ratio from a few % to about 10%. With such a constitution, only the specified wavelength becomes an oscillated state, thus the pumping light having a stable wavelength is obtained.

[0041] Fig. 6 is an example where a bandpass optical filter 14, which selectively transmits only the light having the specified wavelength, is arranged instead of the fiber grating 13. According to this constitution, only light having only the specified wavelength is output from the pumping light source as the pumping light. In either constitution, the wavelength of the pumping light output from the pumping light source can be variably controlled. For example, in the constitution where the fiber grating 13 shown in Fig. 5 is used, the wavelength of the pumping light can be controlled by changing a period of the fiber grating 13. In the constitution where the optical filter 14 shown in Fig. 6 is used, the wavelength of the pumping light can be controlled by changing an angle of incidence to a dielectric multilayer.

[0042] Next, in the optical amplifier of the present invention, description will be made for the constitution where the optical amplification by Raman amplification and the normal optical amplification are used in combination. Although the above-described optical amplifier of the present invention shows the optical amplification independently by Raman amplification function, the normal optical amplification can be used in combination.

[0043] Fig. 7 is a view showing the constitution of the second embodiment of the optical amplifier of the present invention. The fundamental constitution is the same as the one shown in Fig. 4. The optical amplifier comprises: a rare-earth element doped fiber (herein, the wavelength of the signal light is set at 1550nm and the erbium doped fiber (EDF) is used) 6 in the previous step of the wavelength multiplexer 3; a pumping light source

7 for outputting the pumping light to allow the amplification medium to be in the excited state; and an optical multiplexer 8, which is arranged in the previous step of the EDF 6, for allowing the pumping light to be incident on the EDF 6 in the same direction as that of the signal light. Herein, an optical isolator 10 is arranged to prevent lights from being incident on the EDF 6. The lights to be prevented from incidence are: the reflected returning light of the WDM signal light, which is amplified and output, from the optical fiber transmission path 1; and the pumping lights (the lights from the right side in the drawing) for Raman amplification, which are sent out from the optical amplifier arranged in the subsequent step.

[0044] The optical multiplexer 8 may be arranged not in the previous step of the EDF 6 but on an output side, making the excitation to be a backward excitation. However, to minimize the influence to Raman amplification, a forward excitation type as shown in Fig. 7 is preferable.

[0045] According to the embodiment, a higher gain can be obtained by combination of the optical amplification by Raman amplification and the normal amplification. Particularly, as shown in Fig. 7, in the constitution where the pumping light sources 4 and 5 for Raman amplification are arranged in the subsequent step of the EDF 6, the EDF 6 is firstly excited by the pumping lights output from the pumping light sources. Since Raman amplification function occurs by the residual pumping light that passed the EDF 6, efficient optical amplification can be performed. Irrespective of an arrangement state of the pumping light sources 4 and 5 for Raman amplification and the pumping light source 7 for the normal optical amplification, the WDM signal light to be input to the EDF 6 is already Raman amplified in the optical fiber transmission path 1 in any arrangement state. Since flatness of the optical output level is maintained, difference of the output level does not increase when the normal optical amplification is performed.

[0046] As described above, assuming that the center wavelength of the WDM signal light is 1550nm, when the peak gain by Raman amplification occurs at the wavelength shorter than that of the pumping light by 90nm, the gain has its peak at the same wavelength as the center wavelength of the signal light, that is 1550nm, in the case where the signal light is Raman amplified by the wavelength at 1440nm. Therefore, in the embodiment, the wavelengths of the pumping lights are set shorter and longer than 1460nm at approximately 1450nm and 1470nm respectively. It is satisfactory that the wavelength output from the pumping light source 7 for performing the normal optical amplification is set at 1480nm or 980nm. If the wavelength of the pumping light for Raman amplification is close to 1480nm, it contributes for the normal optical amplification function when the pumping light passes the EDF 6.

[0047] Next, description will be made for the third embodiment of the optical amplifier of the present invention.

[0048] Fig. 8 is a view showing the constitution of the

third embodiment of the optical amplifier of the present invention. The embodiment is characterized in that uniformity of the optical output level of each signal light is detected with regard to the Raman amplified WDM signal light, and the feedback control is performed for Raman amplification function.

[0049] As shown in Fig. 8, the fundamental constitution is the same as that of the variation example of the first embodiment shown in Fig. 4. In the embodiment, a part of the Raman amplified WDM signal light is split by an optical splitter 15 arranged in the previous step of the wavelength multiplexer 3. Two signal lights having the wavelengths different from each other are further extracted from the split WDM signal light, and are converted into electric signal by optical receivers 19 and 20 respectively, and the optical output levels are detected.

[0050] The optical output levels of the both signal lights are input to a pumping light output control circuit 21 to compute the difference, and the pumping light sources 4 and 5 are controlled according to the difference, that is, the uniformity (gradient of the gain to the wavelength). Since this control is the one to adjust the flatness of the gain in Raman amplification by each pumping light, the control is achieved by adjusting the pumping light output itself or the wavelength. The pumping light output level itself can be variably controlled by an injected current to the laser diode, and, as described above, the wavelength of the pumping light output can be variably controlled.

[0051] Herein, although optional two signal lights in the signal lights included in the WDM signal light are extracted, the two signal lights having the wavelengths different from each other as much as possible are preferably extracted from the viewpoint of computing the uniformity more accurately. In the embodiment, the split WDM signal light is further split into two lights by an optical splitter 16, and the signal lights are extracted from optical filters 17 and 18, which selectively transmit only light having the wavelength to be extracted. Extraction of the signal light can be also performed by sweeping by using a wavelength variable optical filter.

[0052] Fig. 9 and Fig. 10 show the constitutions of the fourth and fifth embodiments of the optical amplifier of the present invention respectively. These embodiments are basically the ones that comprise the feedback control function for the Raman amplified WDM signal light similarly to the third embodiment shown in Fig. 8. However, the embodiments, similarly to the second embodiment shown in Fig. 7, comprise the feedback control function in the constitution where the normal optical amplification is used in combination with Raman amplification. In the fourth embodiment shown in Fig. 9, the flatness of the WDM signal light, which is amplified only by Raman amplification, is detected to perform the feedback control. On the other hand, difference can be seen in the fifth embodiment shown in Fig. 10, where the feedback control is performed for the WDM signal light on which the normal optical amplification was performed in

addition to Raman amplification.

[0053] Next, description will be made for the embodiments of the present invention with regard to the optical amplification repeater, which is arranged midway of each of the upper and lower lines, having a function to perform optical repeating and amplification on the signal light transmitting along each line.

[0054] Fig. 11 shows the constitution of the first embodiment of the optical amplification repeater of the present invention. As the constitution for performing the optical amplification by Raman amplification on the both signal lights propagating in the upper and lower lines, a constitution is considered that the optical amplifiers of the present invention are simply provided in both of the upper and lower lines. Herein, for establishing the more efficient constitution, the optical amplification repeater is characterized in that the two pumping light sources 4 and 5 for Raman amplification use are commonly used by the upper and lower lines as shown in Fig. 11. Pumping lights  $\lambda_1$  and  $\lambda_2$  respectively output from the pumping light sources 4 and 5 are temporarily coupled in an optical splitting coupler 9. The coupled pumping lights are directly split into two lights to be output to wavelength multiplexers 3a and 3b arranged for the upper and lower lines, from which the pumping lights are sent out to the optical fiber transmission path 1 (broken lines in the drawing).

[0055] As the optical splitting couplers, optical multiplexers, optical demultiplexers, wavelength multiplexers and the like used in the present invention, ones using the dielectric multilayer, fusion type couplers or the like can be applied.

[0056] Fig. 12 and Fig. 13 respectively show the constitutions of the second and third embodiments of the optical amplification repeater of the present invention. In the embodiments, similarly to the second embodiment of the optical amplifier of the present invention shown in Fig. 7, the pumping light sources for the normal optical amplification are used in combination with the ones for Raman amplification. In the second embodiment shown in Fig. 12, pumping light sources 7a and 7b for performing the normal optical amplification are separately provided in the upper and lower lines. On the other hand, in the third embodiment shown in Fig. 13, the pumping light sources are commonly used by the upper and lower lines, and the pumping lights are coupled and split by an optical splitting coupler 11 that functions similarly to the optical splitting coupler 9, which was described in the first embodiment of the optical amplification repeater of the present invention in Fig. 11. Thus, it is possible to allow the pumping light sources to have redundancy, and a more reliable optical amplification repeater can be constituted. With regard to the pumping lights for performing the normal optical amplification, their routes are shown in chain lines in the drawing.

[0057] Next, description will be made for the WDM signal light transmission apparatus using the optical am-



plifier or the optical amplification repeater of the present invention.

[0058] Fig. 14 shows the constitution of the first embodiment of the WDM signal light transmission apparatus of the present invention, which is the signal light transmission apparatus for performing a light transmission in one direction. Fig. 15 shows the constitution of the second embodiment of the WDM signal light transmission apparatus of the present invention, which performs the light transmission in both directions.

[0059] Referring to Fig. 14, the WDM signal light transmission apparatus of the embodiment comprises: an optical transmission terminal station 22 for sending out the WDM signal light, in which a plurality of signal lights having the wavelengths different from each other are wavelength multiplexed; an optical fiber transmission path 29 (29a, 29b, 29c) for propagating the WDM signal light; an optical receiving terminal station 23 for receiving the WDM signal light; and optical amplifiers 24 (24a, 24b) arranged midway of the optical transmission path to repeat and amplify the WDM signal light. As the optical amplifiers 24 (24a, 24b), any one of the above-described embodiments of the present invention can be applied.

[0060] The optical transmission terminal station 22, for example, as shown in Fig. 14, can be constituted of optical transmitters 25 for sending out the signal lights having each wavelength (channel) and an optical multiplexer 26 for sending out the signal lights to the optical fiber transmission path 29a after wavelength multiplexing. On the other hand, optical receiving terminal station 23 comprises: an optical demultiplexer 27 for demultiplexing the WDM signal light sent out from the optical fiber transmission path 29c; and optical receivers 28 for receiving the demultiplexed signal lights respectively.

[0061] In the embodiment, the two optical amplifiers 24a and 24b are arranged in the optical fiber transmission path 29 as an example. With regard to the optical amplifier 24a, the pumping light for Raman amplification is sent out to the optical fiber transmission path 29a where the WDM signal light is Raman amplified, and input to the optical amplifier 24a. For the optical amplifier 24b, the pumping light is sent out to the optical fiber transmission path 29b where Raman amplification is performed.

[0062] The second embodiment of the WDM signal light transmission apparatus of the present invention shown in Fig. 15 shows the WDM signal light transmission apparatus that comprises the upper and lower lines, and transmits the WDM signal lights in both directions. Similarly to the first embodiment shown in Fig. 14, the WDM signal light transmission apparatus of the embodiment comprises: an optical transmission terminal station 22a for sending out the down WDM signal light, in which a plurality of down signal lights having the wavelengths different from each other are wavelength multiplexed; the optical fiber transmission path 29 (29a, 29b, 29c) for propagating the down WDM signal light;

an optical receiving terminal station 23a for the down signal light for receiving the down WDM signal light; an optical transmission terminal station 22b for sending out the up WDM signal light, in which a plurality of up signal lights having the wavelengths different from each other are wavelength multiplexed; an optical fiber transmission path 30 (30a, 30b, 30c) for the up signal light for propagating the up WDM signal light; an optical receiving terminal station 23b for the up signal light for receiving the up WDM signal light; and the optical amplifiers 24 (24a, 24b) of the present invention. The optical amplifiers 24 (24a, 24b), which are arranged in the midway of the upper and lower optical fiber transmission paths, repeat and amplify the up and down WDM signal lights respectively. As the optical amplifiers 24 (24a, 24b), any one of the above-described embodiments of the present invention can be applied.

[0063] As described above, the optical amplifier of the present invention comprises: the two (first and second) pumping light sources for Raman amplification for outputting the first and second pumping lights; the wavelength multiplexer for Raman amplification for allowing the first and second pumping lights to be incident on the optical fiber transmission paths, where the WDM signal light propagates, in the direction opposite to the propagation direction of the signal light. The signal lights are Raman amplified by the both pumping lights. In this case, the wavelength of the first pumping light is set such that the gain of the Raman amplified signal light declines in the right direction, and, on the other side, the wavelength of the second pumping light is set such that the gain declines in the left direction.

[0064] Therefore, the gain characteristic has higher uniformity in comparison with the one obtained when the signal light is Raman-amplified by independent pumping light. Also, when the WDM signal light is amplified in optical amplification utilizing a Raman amplification function, the uniformity of the gain (optical output level) is maintained. Accordingly, the wavelength characteristic of the WDM signal light to be input to the optical amplifier can be controlled not to change by Raman amplification or to be in a state of a fixed-wavelength characteristic always. Although the wavelength characteristic of Raman amplification depends on the wavelength of the pumping light, fixing the wavelength of the pumping light by the wavelength-selective optical reflector enables more stable optical amplification by Raman amplification.

[0065] While this invention has been described in connection with certain preferred embodiments, it is to be understood that the subject-matter encompassed by way of this invention is not to be limited to those specific embodiments. On the contrary, it is intended for the subject-matter of the invention to include all alternatives, modifications and equivalents as can be included within the scope of the following claims.

[0066] Each feature disclosed in this specification (which term includes the claims) and/or shown in the

drawings may be incorporated in the invention independently of other disclosed and/or illustrated features.

[0067] The text of the abstract filed herewith is repeated here as part of the specification.

[0068] Flatness of a gain (optical output level) is maintained even when wavelength-division-multiplexed signal light (WDM signal light) is optically amplified utilizing a Raman amplification function. The optical amplifier comprises: two (first and second) pumping light sources for Raman amplification for outputting first and second pumping lights; wavelength multiplexers for Raman amplification for allowing the first and second pumping lights to be incident on optical fiber transmission paths, where the WDM signal light propagates, in the direction opposite to the propagation direction of the signal light. The signal lights are Raman-amplified by the pumping lights. A wavelength of the first pumping light is set such that the gain of the Raman-amplified signal light declines in one direction, and, on the other side, the wavelength of the second pumping light is set such that the gain declines in the other direction. Gradients for showing a relation between the wavelength and the gain in Raman amplification by the first and second pumping lights are made to be in opposite directions from each other. Optical output levels and the wavelengths of the first and second pumping lights are set such that the gains for the signal lights included in the Raman-amplified WDM signal light become substantially equal to one another.

#### Claims

#### 1. An optical amplifier, comprising:

a first pumping light source for Raman amplification, which outputs a first pumping light having a first wavelength;

a second pumping light source for Raman amplification, which outputs a second pumping light having a second wavelength; and,

wavelength-multiplexer means for Raman amplification, which allows said first and second pumping lights to be incident on an optical fiber transmission path where a signal light propagates;

wherein said signal light is Raman-amplified in said optical fiber transmission path by said first and second pumping lights.

#### 2. The optical amplifier according to claim 1,

wherein said wavelength-multiplexer means for Raman amplification allows said first and second pumping lights to be incident on said optical fiber transmission path in an opposite direction to a propagation direction of said signal light.

#### 3. The optical amplifier according to claim 1,

wherein said wavelength-multiplexer means for Raman amplification allows said first and second pumping lights to be incident on said optical fiber transmission path in the same direction as the propagation direction of said signal

#### 4. The optical amplifier according to claim 1,

wherein said signal light is a wavelength-division-multiplexed signal light (a WDM signal light), in which signal light having a plurality of wavelengths different from each other are wavelength-division-multiplexed.

#### 5. The optical amplifier according to claim 4,

wherein said first wavelength is a wavelength allowing said signal light to be Raman-amplified such that the wavelength having a peak gain by Raman amplification becomes shorter than the wavelength of the signal light included in said WDM signal light; and,

said second wavelength is a wavelength allowing said signal light to be Raman-amplified such that the wavelength having the peak gain by Raman amplification becomes longer than the wavelength of the signal light included in said WDM signal light.

#### 6. The optical amplifier according to claim 5;

wherein a gradient showing a relation between the wavelength and the gain in Raman amplification by said first pumping light and a gradient showing the relation between the wavelength and the gain in Raman amplification by said second pumping light are in opposite directions from each other; and,

an optical output level and the wavelength of said first and second pumping lights are respectively set such that the gains for signal lights included in said WDM signal light, on which Raman amplification was performed by said first and second pumping lights, become substantially equal to each other.

#### 7. The optical amplifier according to claim 4,

wherein said first pumping light source for Raman amplification comprises:

a first laser diode for oscillating a first light; and,

a first wavelength-selective optical reflector for transmitting said first-wavelength light in a specified ratio and reflecting a residual light previously created by said first laser diode; and,

said second pumping light source for Raman amplification comprises:

a second laser diode for oscillating a second light; and,  
a second wavelength-selective optical reflector for transmitting said second-wavelength light in a specified ratio and reflecting a residual light previously created by said second laser diode.

8. The optical amplifier according to claim 4,

wherein said first pumping light source for Raman amplification comprises:

a first laser diode for oscillating a first light; and,  
a first optical filter for selectively transmitting said first-wavelength light previously created by said first laser diode; and,

said second pumping light source for Raman amplification comprises:

a second laser diode for oscillating a second light; and,  
a second optical filter for selectively transmitting said light of a second-wavelength light previously created by said second laser diode.

9. The optical amplifier according to claim 4,

wherein said wavelength multiplexer for Raman amplification comprises:

a first pumping-light multiplexer for Raman amplification, which transmits said signal light and allows said first pumping light to be incident on an optical fiber, the multiplexer being connectable to said optical fiber connectable to said optical fiber transmission path; and,  
a second pumping-light multiplexer for Raman amplification, which transmits said signal light and allows said second pumping light to be incident on the optical fiber, the multiplexer being connectable to said optical fiber connectable to said optical fiber transmission path.

10. The optical amplifier according to claim 4,

wherein said wavelength multiplexer for Raman amplification comprises:

a pumping-light multiplexer for Raman amplification, which multiplexes said first and second pumping lights and outputs a multiplexed pumping light; and,  
a pumping-light multiplexer for Raman amplifi-

cation, which transmits said signal light and allows said multiplexed pumping light to be incident on an optical fiber, the multiplexer being connectable to said optical fiber connectable to said optical fiber transmission path.

11. The optical amplifier according to claim 4, wherein said wavelength multiplexer for Raman amplification comprises:

a polarization combiner for Raman amplification for performing a polarization combination on said first and second pumping lights and outputs the multiplexed pumping light, where said first and second pumping lights respectively output from said first and second pumping-light sources for Raman amplification are perpendicular to each other, that is, in a polarization state; and,  
a pumping-light multiplexer for Raman amplification, which transmits said signal light and allows said multiplexed pumping light to be incident on an optical fiber, and multiplexer being connectable to said optical fiber connectable to said optical fiber transmission path.

12. The optical amplifier according to claim 4, further comprising:

an amplification medium for amplifying said signal light;  
a third pumping light source for outputting a third pumping light to allow said amplification medium to be in an excited state; and,  
a wavelength multiplexer for allowing said third pumping light to be incident on said amplification medium.

13. The optical amplifier according to claim 12,

wherein said wavelength multiplexer is arranged on a side from which the signal light is input with respect to said amplification medium; and,  
said third pumping light is allowed to be incident on the amplification medium in the same direction as the propagation direction of said signal light.

14. The optical amplifier according to claim 12,

wherein said wavelength multiplexer is arranged on a side to which the signal light is output from said amplification medium; and,  
said third pumping light is allowed to be incident on the amplification medium in an opposite direction to the propagation direction of said signal light.

15. The optical amplifier according to claim 4, further comprising:

an optical isolator for selectively transmitting only light propagating to the same direction as said signal light and obstructing light propagating in the opposite direction, the optical isolator being arranged on a side of said wavelength multiplexer to which said signal light for Raman amplification is output.

16. The optical amplifier according to claim 4 or 12, further comprising:

an optical splitter for splitting a part of said WDM signal light and outputting a split WDM signal light;  
signal-light extracting means for extracting two signal lights, which have wavelengths different from each other, from each signal light included in said split WDM signal light;  
an optical receiver for detecting the optical output level of each of the two signal lights extracted by said signal-light extracting means; and,  
a pumping-light output-control circuit for controlling any one of the optical output levels and the wavelengths of said first and second pumping lights for Raman amplification according to an amount of difference between said two optical output levels.

17. The optical amplifier according to claim 16,

wherein said optical splitter is arranged on a side from which said WDM signal light is input to said wavelength multiplexer for Raman amplification.

18. The optical amplifier according to claim 16,

wherein said optical splitter is arranged on a side to which said WDM signal light is output from said wavelength multiplexer for Raman amplification.

19. An optical amplification repeater, comprising:

an optical amplifier for a down signal, which is arranged in an optical fiber transmission path for the down signal; and,  
an optical amplifier for an up signal, which is arranged in an optical fiber transmission path for the up signal;  
wherein said optical amplifier for the down signal includes the optical amplifier according to any one of claims 4 to 11; and,  
said optical amplifier for the up signal includes the optical amplifier according to any one of claims 4 to 11.

20. An optical amplification repeater, comprising:

an optical amplifier for a down signal, which is arranged in an optical fiber transmission path for the down signal and,

an optical amplifier for an up signal, which is arranged in an optical fiber transmission path for the up signal;

wherein said optical amplifier for the down signal includes the optical amplifier according to claim 12; and,

said optical amplifier for the up signal includes the optical amplifier according to claim 12.

21. The optical amplification repeater according to claim 19 or 20,

wherein said first pumping light source for Raman amplification, which is provided in said optical amplifier for the down signal, and said first pumping light source for Raman amplification, which is provided in the optical amplifier for the up signal, are a common first pumping light source for Raman amplification; and,  
said second pumping light source for Raman amplification, which is provided in said optical amplifier for the down signal, and said second pumping light source for Raman amplification, which is provided in said optical amplifier for the up signal, are a common second pumping light source for Raman amplification,  
the optical amplification repeater comprising:

an optical coupler for coupling and splitting first and second pumping lights for Raman amplification output from said common first and said common second pumping light sources for Raman amplification and respectively outputting the split pumping lights to said wavelength multiplexer for Raman amplification, which is provided in said optical amplifier for the down signal, and said wavelength multiplexer for Raman amplification, which is provided in said optical amplifier for the up signal.

22. The optical amplification repeater according to claim 21,

wherein said third pumping light source provided in said optical amplifier for the down signal and said third pumping light source provided in said optical amplifier for the up signal are a common third pumping light source;

the optical amplification repeater comprising:

the optical coupler for coupling and splitting the third pumping lights output from said third common pumping light source and respectively outputting the split pumping lights to said wavelength multiplexer provided in said optical amplifier for the down signal and said wavelength multiplexer provided in said optical

amplifier for the up signal.

23. The optical amplification repeater according to claim 21,

wherein said optical amplifier for the down signal and said optical amplifier for the up signal further comprises respectively fourth pumping light sources, each of which outputs a fourth pumping light to make said amplification medium in an excited state;

said third pumping light source provided in said optical amplifier for the down signal and said third pumping light source provided in said optical amplifier for the up signal are a common third pumping light source; and,

said fourth pumping light source provided in said optical amplifier for the down signal and said fourth pumping light source provided in said optical amplifier for the up signal are a common fourth pumping light source;

the optical amplification repeater comprising:

the optical coupler for coupling and splitting the third pumping light output from said third common pumping light source and the fourth pumping light output from said common fourth pumping light source and respectively outputting the split pumping lights to said wavelength multiplexer provided in said optical amplifier for the down signal and said wavelength multiplexer provided in said optical amplifier for the up signal.

24. A transmission apparatus of wavelength-division-multiplexed signal light, comprising:

an optical transmission terminal station for wavelength-division-multiplexing a plurality of signal lights having the wavelengths different from each other and for sending out a wavelength division multiplexed signal light (a WDM signal light) ;

an optical fiber transmission path for propagating said WDM signal light;

an optical receiving terminal station for receiving said WDM signal light; and,

the optical amplifier according to claim 4, which is arranged in the midway of said optical fiber transmission path to repeat and amplify said WDM signal light.

25. A transmission apparatus of wavelength-division-multiplexed signal light, comprising:

an optical transmission terminal station for wavelength-division-multiplexing a plurality of down signal lights having the wavelengths different from each other and for sending out a

down wavelength-division-multiplexed signal light (a WDM signal light) ;

an optical fiber transmission path for the down signal light for propagating said down WDM signal light;

an optical fiber transmission path for the down signal light for propagating said down WDM signal light;

an optical receiving terminal station for the down signal light for receiving said down WDM signal light;

an optical transmission terminal station for wavelength-division-multiplexing a plurality of up signal lights having the wavelengths different from each other and for sending out an up WDM signal light;

an optical fiber transmission path for the up signal light for propagating said up WDM signal light;

an optical receiving terminal station for the up signal light for receiving said up WDM signal light; and,

the optical amplifiers according to claim 12, which are arranged midway of said up and down optical fiber transmission paths to repeat and amplify said up and down WDM signal lights.

Fig. 1




Fig. 2




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 3D






Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12






Fig. 13




Fig. 14





Fig. 15



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 1 143 645 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
02.01.2003 Bulletin 2003/01

(51) Int Cl.7: **H04B 10/17**, **H01S 3/30**,  
**H04J 14/02**

(43) Date of publication A2:  
10.10.2001 Bulletin 2001/41

(21) Application number: **01301940.1**

(22) Date of filing: **02.03.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU**  
**MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Yokoyama, Ryu, Nec Corporation**  
**Tokyo (JP)**

(30) Priority: **02.03.2000 JP 2000057290**


(74) Representative: **Moir, Michael Christopher et al**  
**Mathys & Squire**  
**100 Gray's Inn Road**  
**London WC1X 8AL (GB)**

(71) Applicant: **NEC CORPORATION**  
**Tokyo (JP)**

(54) **Optical amplifier, optical amplifying repeater and transmission apparatus for wavelength-division-multiplexed signal light**

(57) Flatness of a gain (optical output level) is maintained even when wavelength-division-multiplexed signal light (WDM signal light) is optically amplified utilizing a Raman amplification function. The optical amplifier comprises: two (first and second) pumping light sources for Raman amplification for outputting first and second pumping lights; wavelength multiplexers for Raman amplification for allowing the first and second pumping lights to be incident on optical fiber transmission paths, where the WDM signal light propagates, in the direction opposite to the propagation direction of the signal light. The signal lights are Raman-amplified by the pumping

lights. A wavelength of the first pumping light is set such that the gain of the Raman-amplified signal light declines in one direction, and, on the other side, the wavelength of the second pumping light is set such that the gain declines in the other direction. Gradients for showing a relation between the wavelength and the gain in Raman amplification by the first and second pumping lights are made to be in opposite directions from each other. Optical output levels and the wavelengths of the first and second pumping lights are set such that the gains for the signal lights included in the Raman-amplified WDM signal light become substantially equal to one another.

**Fig. 1**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 30 1940

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Incl.7)
X	WO 00 05622 A (AKASAKA YUICHI ; EMORI YOSHIHIRO (JP); NAMIKI SHU (JP); FURUKAWA E) 3 February 2000 (2000-02-03) & EP 1 018 666 A (FURUKAWA ELECTRIC CO LTD) 12 July 2000 (2000-07-12) ---	1-8,10, 11, 16-18,24	H04B10/17 H01S3/30 H04J14/02
X	US 5 883 736 A (OGOSHI HARUKI ET AL) 16 March 1999 (1999-03-16) ---	1-4,7-14	
Y	* column 4, line 39 - line 58 * * column 3, line 36 - line 40 * * column 5, line 9 - column 6, line 3 * * figures 3,4 * ---	19-23,25	
X	EP 0 911 926 A (NIPPON TELEGRAPH & TELEPHONE) 28 April 1999 (1999-04-28) * abstract * * figures 16,24,33,36A,37A * ---	1,3,4,9, 15,24	
Y	US 5 280 549 A (BARNARD CHRIS. ET AL) 18 January 1994 (1994-01-18) * column 9, line 51 - line 68 * * figure 8 * ---	19-23,25	
A	US 5 323 404 A (GRUBB STEPHEN G) 21 June 1994 (1994-06-21) * abstract * * column 7, line 41 - line 56 * -----	7,8	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>5 November 2002</b>	Examiner <b>Reville, L</b>
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1803 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 1940

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-11-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0005622	A	03-02-2000	JP	2000105395 A	11-04-2000
			JP	2000098433 A	07-04-2000
			EP	1018666 A1	12-07-2000
			WO	0005622 A1	03-02-2000
			US	6292288 B1	18-09-2001
			US	2002085267 A1	04-07-2002
			US	2001046083 A1	29-11-2001
			US	2002021487 A1	21-02-2002
US 5883736	A	16-03-1999	JP	9230399 A	05-09-1997
			FR	2745395 A1	29-08-1997
			IT	RM970096 A1	21-08-1998
EP 0911926	A	28-04-1999	JP	11084440 A	26-03-1999
			EP	0911926 A1	28-04-1999
			US	6172803 B1	09-01-2001
			JP	10294510 A	04-11-1998
			WO	9836479 A1	20-08-1998
US 5280549	A	18-01-1994	CA	2093259 A1	03-10-1994
US 5323484	A	21-06-1994	DE	69427673 D1	16-08-2001
			DE	69427673 T2	25-04-2002
			EP	0651479 A1	03-05-1995
			JP	2813145 B2	22-10-1998
			JP	7181529 A	21-07-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**